

Suburban Stair Systems: Speckled & Solid

Style	Suburban Speckled Stair Tread	Suburban Speckled Stair Tread with Visually Impaired Safety Tread
Construction	Thermoset Vulcanized Rubber - Type TS ASTM	Thermoset Vulcanized Rubber - Type TS
Classification	F2169 Class II, Group 1 & 2	ASTM F2169 Class II, Group 1 & 2
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Square and Sculptured	Square and Sculptured
Profile - Nose	90° angle	90° angle
Sizes	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m)	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m) Abrasive Insert 2" (.50 mm)
Colors	36	36 Tread Colors, 10 Abrasive Tape Colors
Packaging	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)
Adhesive	ML260 Acrylic Adhesive Double Sided Tape	

Testing

HUD/FHA	Passes
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85
Thickness (ASTM 386)	$\pm 1/32"$ (0.8 mm)
Static Load (ASTM F970)	Passes - Residual Indent $\leq 0.005"$
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change

Environmental Data

Indoor Air Quality	FloorScore Certified
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials

Warranty

Limited 10-Year Commercial Warranty
 Limited 10-Year Wear Warranty
 Limited 5-Year Nose Warranty

Suburban Finishing Touch

Style	Suburban Solid Stair Tread	Suburban Solid Stair Tread with Visually Impaired Safety Tread
Construction	Thermoset Vulcanized Rubber - Type TS	Thermoset Vulcanized Rubber - Type TS
Classification	ASTM F2169 Class II, Group 1 & 2	ASTM F2169 Class II, Group 1 & 2
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Round, Square, and Sculptured	Round, Square, and Sculptured
Profile - Nose	90° angle	90° angle
Sizes	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m)	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m) Abrasive Insert 2" (.50 mm)
Colors	36	36 Tread Colors, 10 Abrasive Tape Colors
Packaging	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)
Adhesive	ML260 Acrylic Adhesive Double Sided Tape	

Testing

HUD/FHA	Passes
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85
Thickness (ASTM 386)	$\pm 1/32"$ (0.8 mm)
Static Load (ASTM F970)	Passes - Residual Indent $\leq 0.005"$
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change

Environmental Data

Indoor Air Quality	FloorScore Certified
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials

Warranty

Limited 10-Year Commercial Warranty
 Limited 10-Year Wear Warranty
 Limited 5-Year Nose Warranty