

Suburban Tile



Style	Suburban Solid Tile	Suburban Speckled Tile
Construction	Thermoset Rubber Tile	Thermoset Rubber Tile
Classification	ASTM F1344 Class I, Type A	ASTM F1344 Class I, Type A
Total Thickness	1/8" (3.175 mm)	1/8" (3.175 mm)
Profiles	Square, Sculptured, Round	Square, Sculptured, Smooth
Sizes	Square - 18.125" x 18.125" (460 x 460 mm), 36.25" x 36.25" (920.75 x 920.75 mm) Sculptured - 18.125" x 18.125" (460 x 460 mm), 36" x 36" (914.4 x 914.4 mm) Round - 18.125" x 18.125" (460 x 460 mm), 36.125" x 36.125" (917.7 x 917.7 mm)	Square - 18.125" x 18.125" (460 x 460 mm), 36.25" x 36.25" (920.75 x 920.75 mm) Sculptured - 18.125" x 18.125" (460 x 460 mm), 36" x 36" (914.4 x 914.4 mm) Smooth - 18" x 18" (457.2 x 457.2 mm), 36" x 36" (914.4 x 914.4 mm)
Finish	Matte	Matte
Colors	36	36
Packaging	18.125" x 18.125" - 20 pcs, 45.625 ft ² (4.239 m ²), 43 lbs (19.5 kg) All other sizes sold per piece.	18" x 18" - 20 pcs, 45 ft ² (4.181 m ²), 42.6 lbs (19.32 kg) 18.125" x 18.125" - 20 pcs, 45.625 ft ² (4.239 m ²), 43 lbs (19.5 kg) All other sizes sold per piece.
Adhesive	CL928 Full Spread, 2-part Urethane ML260 Full Spread, General Purpose Acrylic Note: Must use CL928 adhesive under hospital beds and heavy rolling loads or where high performance is needed.	CL928 Full Spread, 2-part Urethane ML260 Full Spread, General Purpose Acrylic Note: Must use CL928 adhesive under hospital beds and heavy rolling loads or where high performance is needed.

Testing

HUD/FHA	Meets or Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.15%
Squareness (ASTM F540)	Passes - Max 0.010'
Hardness (ASTM D2240)	Passes - Shore Type A
Static Load (ASTM F970)	Passes
Static Load (ASTM F970 mod.)	Passes
Flooring Radiant Panel (ASTM E648)	Passes
Smoke Density (ASTM E662)	Passes
Slip Resistance (ASTM C1028, Dry)	Passes
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change

Environmental Data

Rapidly Renewable Content Indoor Air Quality	Contains 4% rapidly renewable resource content FloorScore Certified
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials

Warranty

Limited 10 Year Commercial Warranty

Limited 10 Year Wear Warranty

- Suburban Solid and Suburban Speckled formulations are made with our superior rubber so they retain their amazing color, resist indentations and cracking, and are quiet underfoot. Built-in waxes produce a natural luster that requires no finish or stripping, lowering maintenance costs.
- Suburban Solid and Suburban Speckled are not recommended in commercial areas that require static dissipation.
- In spaces that will receive rubber flooring and accessories, maintain a minimum temperature of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in product appearance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substance from being tracked onto floor.