

Suburban Finishing Touch

Style	Franklin, Chair Rail, Dearborn, Richmond	Yonkers
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/4" (6.35 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Profile Height	Franklin, Dearborn, Richmond - 4" or 4 1/4" Chair Rail - 4" Dearborn - 6"	6"
Colors	40 (36 are Coordination)	40 (36 are Coordination)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	KL463 Acrylic	KL463 Acrylic

Testing

HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change

Environmental Data

Indoor Air Quality	FloorScore Certified
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials

Warranty

Limited 5-Year Commercial Warranty

Suburban Finishing Touch

Style	Ashburn, Evanston, Preserve, York	Cary, York, Dearborn, Slidell, Decatur, Alpine, Richmond, Tarpon*
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	5/16" (7.94 mm)	3/8" (9.52 mm)
Profile	Smooth	Smooth
Profile Height	Evanston - 3" Ashburn, Preserve, York - 4" or 4 1/2" York - 6"	Cary - 3" Clayton - 3 1/4" Dearborn, Richmond - 4" Cary, Dearborn, Slidell, Decatur, Tarpon - 4 1/4" Alpine - 5 1/4"
Colors	40 (36 are Coordination)	40 (36 are Coordination)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	KL463 Acrylic	KL463 Acrylic

Testing

HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change

Environmental Data

Indoor Air Quality	FloorScore Certified
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRC5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials

Warranty

Limited 5-Year Commercial Warranty

Suburban Finishing Touch

Style	Quarter Round	Pre-mitered Inside and Outside corners also available
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/2" (12.7 mm)	
Profile	Smooth	Smooth
Colors	40 (36 are Coordination)	40 (36 are Coordination)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	KL463 Acrylic	KL463 Acrylic

Testing

HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change

Environmental Data

Indoor Air Quality	FloorScore Certified
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials

Warranty

Limited 5-Year Commercial Warranty

Suburban Finishing Touch Packaging

Style	Total Thickness	8' Lengths Pcs Per Carton	8' Lengths LF Per Carton	8' Lengths Carton Weight	Inside/Outside Corners Pcs Per Carton	Carton Weight
Cary 3"	3/8"	8	64 lf (19.51 m)	33 lbs (14.97 kg)	20	5 lbs (2.268 kg)
Cary 4¼"	3/8"	8	64 lf (19.51 m)	51 lbs (23.13 kg)	20	8 lbs (3.629 kg)
Ashburn 4"	5/16"	6	48 lf (14.63 m)	59 lbs (26.76 kg)	20	14 lbs (6.35 kg)
Ashburn 4½"	5/16"	6	64 lf (19.51 m)	81 lbs (36.74 kg)	20	16 lbs (7.257 kg)
Franklin 4"	1/4"	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Franklin 4¼"	1/4"	8	64 lf (19.51 m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
*Chair Rail 4"	1/4"	5	60 lf (18.29 m)	46 lbs (20.87 kg)	20	n/a
Yonkers 6"	3/16"	4	32 lf (9.754 m)	43 lbs (19.5 kg)	20	18 lbs (8.165 kg)
Dearborn 4"	1/4"	8	64 lt (19.51m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Dearborn 4"	3/8"	8	48 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Dearborn 4¼"	1/4"	8	64 lt (19.51m)	63 lbs (28.58 kg)	20	10 lbs (4.536 kg)
Dearborn 6"	1/4"	4	32 lf (9.754 m)	54 lbs (24.49 kg)	20	24 lbs (10.89 kg)
Evanston 3"	5/16"	8	64 lt (19.51m)	52 lbs (23.59kg)	20	9 lbs (4.082 kg)
Slidell 4¼"	3/8"	8	64 lt (19.51m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)
Clayton 3¼"	3/8"	8	64 lt (19.51m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Preserve 4"	5/16"	8	64 lt (19.51m)	77 lbs (34.93 kg)	20	14 lbs (6.35 kg)
Preserve 4½"	5/16"	8	64 lt (19.51m)	81 lbs (36.74 kg)	20	16 lbs (7.257 kg)
Decatur 4¼"	3/8"	8	64 lt (19.51m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)
*Qtr Round ½"	1/2"	20	240 lf (73.15 m)	35 lbs (15.88 kg)	n/a	n/a
Alpine 5 ¼"	3/8"	3	24 lf (7.315 m)	42 lbs (19.05 kg)	20	21 lbs (9.525 kg)
Richmond 4"	1/4"	8	64 lt (19.51m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Richmond 4"	3/8"	8	64 lt (19.51m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Richmond 4¼"	1/4"	8	64 lt (19.51m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
Richmond 4¼"	3/8"	8	64 lt (19.51m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
York 4"	5/16"	6	48 lf (14.63 m)	60 lbs (27.22 kg)	20	16 lbs (7.257 kg)
York 4½"	5/16"	6	48 lf (14.63 m)	63 lbs (28.58 kg)	20	11 lbs (4.99 kg)
York 6"	5/16"	4	32 lf (9.754 m)	54 lbs (24.49 kg)	20	24 lbs (10.89 kg)
York 4¼"	3/8"	8	64 lt (19.51m)	53 lbs (24.04 kg)	20	9 lbs (4.082kg)

* Indicates Ships in 12' Lengths