

Suburban Stair Systems: Seamless Step

Style	Suburban Seamless Step Tread/Riser Combination	Risers/Stringers
Construction	Thermoset Vulcanized Rubber - Type TS	Thermoset Vulcanized Rubber - Type TS
Finish	Matte	Matte
Classification	ASTM F2169 Class 2, Group 1 & 2, Grade 1	ASTM F2169 Class 1, Grade 1
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Round, Sculptured (Solid Colors Only) Sculptured (Speckled Colors Only)	Smooth
Profile - Nose	Square	N/A
Sizes	3' (.91m) 4' (1.22m) 5' (1.52m) 6' (1.83m)	3' (.91m) 4' (1.22m) 5' (1.52m) 6' (1.83m)
Height	9.5" - 13" step depths	7" coved riser/ 12"x36" length stringer
Colors	72 (36 Solid, 36 Speckled)	36
Packaging	5 pcs/carton (3' - 7lbs/pc - 35lbs; 4' - 9lbs/pc - 45lbs; 5' -11.5 lbs/pc - 57.5 lbs; 6' - 14 lbs/pc - 70 lbs)	20 pcs/carton (3' - 36 lbs; 4' - 50 lbs; 5' - 62 lbs; 6' - 74 lbs); (Stringers 12 x 26 - 64 lbs)
Adhesive	ML260 Acrylic Adhesive Double-Sided tape TD315 Epoxy caulk (optional) Used for the visually impaired with contrasting strip color	KL463 Acrylic Adhesive ML260 Acrylic Adhesive

Testing

HUD/FHA	Passes
Hardness (ASTM D2240)	Passes
Flooring Radiant Panel (ASTM E648)	Passes - Shore Type A \geq 85
Smoke Density (ASTM E662)	Passes - Class 1; \geq 0.45 watts/cm ²
Slip Resistance (ASTM C1028, Dry)	Passes - < 450
Chemical Resistance (ASTM F925)	Passes - \geq 0.5 Leather; 0.6 Rubber
Resistance to Heat (ASTM F1514)	Passes - No More Than Slight Change - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/ ASTM E2180)	Passes - No More Than Slight Change

Environmental Data

Indoor Air Quality	FloorScore Certified
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials

Warranty

Limited 10-Year Commercial Warranty
 Limited 10-Year Wear Warranty
 Limited 5-Year Nose Warranty