

community

suburban collection



## finishing touch

Sculptured Rubber Wall Base

An architectural accent, creating the elegant effect of a milled wood base without the expensive installation, indentations, scuffs, and abrasions. Requires no nailing, priming, or painting. Co-extruded thermoplastic rubber is engineered for flexible application to walls, corners, and columns.

# Finishing Touch Sculptured Wall Base



**Cary**  
Height: 3", 4 1/4"  
Thickness: 3/8"  
8' lengths (64 lf per carton)



**Ashburn**  
Height: 4", 4 1/2"  
Thickness: 5/16"  
4": 8' lengths (32 lf per carton)  
4 1/2": 8' lengths (32 lf per carton)



**Franklin**  
Height: 4", 4 1/4"  
Thickness: 1/4"  
8' lengths (64 lf per carton)



**Yonkers**  
Height: 6"  
Thickness: 3/16"  
8' lengths (32 lf per carton)



**Dearborn**  
Height: 4", 4 1/4", 6"  
Thickness: 1/4", 3/8"  
4", 4 1/4": 8' lengths (64 lf per carton)  
6": 8' lengths (32 lf per carton)



**Evanston**  
Height: 3"  
Thickness: 5/16"  
8' lengths (64 lf per carton)



**Slidell**  
Height: 4 1/4"  
Thickness: 3/8"  
8' lengths (64 lf per carton)



**Clayton**  
Height: 3 1/4"  
Thickness: 3/8"  
8' lengths (64 lf per carton)



**Decatur**  
Height: 4 1/4"  
Thickness: 3/8"  
8' lengths (64 lf per carton)

# Finishing Touch Sculptured Wall Base



**Alpine**  
Height: 5 1/4"  
Thickness: 3/8"  
8' lengths (32 lf per carton)



**Tarpon**  
Height: 4 1/4"  
Thickness: 3/8"  
8' lengths (64 lf per carton)



**York**  
Height: 4", 4 1/2", 6"  
Thickness: 3/8", 5/16"  
8' lengths (32 lf per carton)



**Preserve**  
Height: 4", 4 1/2"  
Thickness: 5/16"  
4": 8' lengths (64 lf per carton)  
4 1/2": 8' lengths (32 lf per carton)



**Richmond**  
Height: 4", 4 1/4"  
Thickness: 1/4", 3/8"  
8' lengths (64 lf per carton) \*size depernent



**Quarter Round**  
Height: 1/2"  
Thickness: 1/2"  
20' lengths (240 lf per carton)



**Chair Rail**  
Height: 4"  
Thickness: 1/4"  
5' lengths (60 lf per carton)

|                    |                       |                        |               |                            |                |                   |                   |                        |                   |                  |                        |                        |                  |
|--------------------|-----------------------|------------------------|---------------|----------------------------|----------------|-------------------|-------------------|------------------------|-------------------|------------------|------------------------|------------------------|------------------|
|                    |                       |                        |               |                            |                |                   |                   |                        |                   |                  |                        |                        |                  |
| CARY<br>3", 4 1/4" | ASHBURN<br>4", 4 1/4" | FRANKLIN<br>4", 4 1/4" | YONKERS<br>6" | DEARBORN<br>4", 4 1/4", 6" | EVANSTON<br>3" | SLIDELL<br>4 1/4" | CLAYTON<br>3 1/4" | PRESERVE<br>4", 4 1/4" | DECATUR<br>4 1/4" | ALPINE<br>5 1/4" | RICHMOND<br>4", 4 1/4" | YORK<br>4", 4 1/2", 6" | TARPON<br>4 1/4" |

# Finishing Touch Sculptured Wall Base Colorways



Almond  
2094




Morning Fog  
2114



Canyon Bluff  
2108



Swirling Smoke  
2005



Black  
2121



Onyx  
2110



Brown  
2100



Straw  
2120



Licorice  
2084



Fossil Gray  
2111



Cream  
2079



Golden Yellow  
2125



Granite Rock  
2092



Baja  
2053



Moss Green  
2083



Poinsettia  
2134



Peanut  
2101



Gray  
2078



Smoke  
2082



Slate Castle  
2119



Stone Gray  
2070



Antique Silver  
2081



Margarita  
2025



Smokehouse Brown  
2113



Magnolia  
2016



Emerald  
2029



Navy  
2130



Azure  
2051



Off White  
2086



Cameo Blue  
2054



Maple Syrup  
2102



Anthracite  
2117



Desert Dune  
2048




Feather Gray  
2118




Butter Pea  
2018




Mountain Pine  
2006




White  
2093



Baroque  
2058



Caramel  
2059



Snow  
2062

Basics Done Right



---

## Finishing Touch Specifications

| Style           | Franklin, Chair Rail, Dearborn, Richmond                                        | Yonkers                                   |
|-----------------|---------------------------------------------------------------------------------|-------------------------------------------|
| Construction    | Co-extruded Thermoplastic Rubber, Type TP                                       | Co-extruded Thermoplastic Rubber, Type TP |
| Classification  | ASTM F1861 Type TP, Group 1                                                     | ASTM F1861 Type TP, Group 1               |
| Finish          | Matte                                                                           | Matte                                     |
| Total Thickness | 1/4" (6.35 mm)                                                                  | 3/16" (4.76 mm)                           |
| Profile         | Smooth                                                                          | Smooth                                    |
| Profile Height  | Franklin, Dearborn, Richmond - 4" or 4 1/4"<br>Chair Rail - 4"<br>Dearborn - 6" | 6"                                        |
| Colors          | 40 (36 are Coordination)                                                        | 40 (36 are Coordination)                  |
| Packaging       | See Packaging Chart, p.5                                                        | See Packaging Chart, p.5                  |
| Adhesive        | KL463 Acrylic                                                                   | KL463 Acrylic                             |

### Testing

---

|                                            |                                                     |
|--------------------------------------------|-----------------------------------------------------|
| HUD/FHA                                    | Meets / Exceeds                                     |
| ADAG (American Disability Act Guidelines)  | Passes                                              |
| Flexibility (ASTM F137)                    | Passes - 1/4" Mandrel - No Crack/Break              |
| Flooring Radiant Panel (ASTM E648)         | Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup> |
| Smoke Density (ASTM E662)                  | Passes - $< 450$                                    |
| Chemical Resistance (ASTM F925)            | Passes - No More Than Slight Change                 |
| Resistance to Heat (ASTM F1514)            | Passes - $< 8$ Delta E Color Change                 |
| Resistance to Mold/Mildew (ASTM G21/E2180) | Passes - No More Than Slight Change                 |

### Environmental Data

---

|                    |                                                                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Indoor Air Quality | FloorScore Certified                                                                                                                                                                      |
| LEED Scoreboard    | May contribute to LEED credits:<br>LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring<br>LEED v4: IEQc2 - Low Emitting Materials |

### Warranty

---

Limited 5-Year Commercial Warranty

---

## Finishing Touch Specifications

| Style           | Ashburn, Evanston, Preserve, York                                    | Cary, Dearborn, Slidell, Decatur, Alpine, Richmond, Tarpon*                                                                      |
|-----------------|----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Construction    | Co-extruded Thermoplastic Rubber, Type TP                            | Co-extruded Thermoplastic Rubber, Type TP                                                                                        |
| Classification  | ASTM F1861 Type TP, Group 1                                          | ASTM F1861 Type TP, Group 1                                                                                                      |
| Finish          | Matte                                                                | Matte                                                                                                                            |
| Total Thickness | 5/16" (7.94 mm)                                                      | 3/8" (9.52 mm)                                                                                                                   |
| Profile         | Smooth                                                               | Smooth                                                                                                                           |
| Profile Height  | Evanston - 3"<br>Ashburn, Preserve, York - 4" or 4 1/2"<br>York - 6" | Cary - 3"<br>Clayton - 3 1/4"<br>Dearborn, Richmond - 4"<br>Cary, Dearborn, Slidell, Decatur, Tarpon - 4 1/4"<br>Alpine - 5 1/4" |
| Colors          | 40 (36 are Coordination)                                             | 40 (36 are Coordination)                                                                                                         |
| Packaging       | See Packaging Chart, p.5                                             | See Packaging Chart, p.5                                                                                                         |
| Adhesive        | KL463 Acrylic                                                        | KL463 Acrylic                                                                                                                    |

### Testing

---

|                                            |                                                     |
|--------------------------------------------|-----------------------------------------------------|
| HUD/FHA                                    | Meets / Exceeds                                     |
| ADAG (American Disability Act Guidelines)  | Passes                                              |
| Flexibility (ASTM F137)                    | Passes - 1/4" Mandrel - No Crack/Break              |
| Flooring Radiant Panel (ASTM E648)         | Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup> |
| Smoke Density (ASTM E662)                  | Passes - < 450                                      |
| Chemical Resistance (ASTM F925)            | Passes - No More Than Slight Change                 |
| Resistance to Heat (ASTM F1514)            | Passes - < 8 Delta E Color Change                   |
| Resistance to Mold/Mildew (ASTM G21/E2180) | Passes - No More Than Slight Change                 |

### Environmental Data

---

|                    |                                                                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Indoor Air Quality | FloorScore Certified                                                                                                                                                                      |
| LEED Scoreboard    | May contribute to LEED credits:<br>LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring<br>LEED v4: IEQc2 - Low Emitting Materials |

### Warranty

---

Limited 5-Year Commercial Warranty

---

## Finishing Touch Specifications

| Style           | Quarter Round                             | Pre-mitered Inside and Outside corners also available |
|-----------------|-------------------------------------------|-------------------------------------------------------|
| Construction    | Co-extruded Thermoplastic Rubber, Type TP | Co-extruded Thermoplastic Rubber, Type TP             |
| Classification  | ASTM F1861 Type TP, Group 1               | ASTM F1861 Type TP, Group 1                           |
| Finish          | Matte                                     | Matte                                                 |
| Total Thickness | 1/2" (12.7 mm)                            |                                                       |
| Profile         | Smooth                                    | Smooth                                                |
| Colors          | 40 (36 are Coordination)                  | 40 (36 are Coordination)                              |
| Packaging       | See Packaging Chart, p.5                  | See Packaging Chart, p.5                              |
| Adhesive        | KL463 Acrylic                             | KL463 Acrylic                                         |

### Testing

---

|                                            |                                                     |
|--------------------------------------------|-----------------------------------------------------|
| HUD/FHA                                    | Meets / Exceeds                                     |
| ADAG (American Disability Act Guidelines)  | Passes                                              |
| Flexibility (ASTM F137)                    | Passes - 1/4" Mandrel - No Crack/Break              |
| Flooring Radiant Panel (ASTM E648)         | Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup> |
| Smoke Density (ASTM E662)                  | Passes - $< 450$                                    |
| Chemical Resistance (ASTM F925)            | Passes - No More Than Slight Change                 |
| Resistance to Heat (ASTM F1514)            | Passes - $< 8$ Delta E Color Change                 |
| Resistance to Mold/Mildew (ASTM G21/E2180) | Passes - No More Than Slight Change                 |

### Environmental Data

---

|                    |                                                                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Indoor Air Quality | FloorScore Certified                                                                                                                                                                      |
| LEED Scoreboard    | May contribute to LEED credits:<br>LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring<br>LEED v4: IEQc2 - Low Emitting Materials |

### Warranty

---

Limited 5-Year Commercial Warranty

## Finishing Touch Sculptured Wall Base Packaging

| Style           | Total Thickness | 8' Lengths Pcs Per Carton | 8' Lengths LF Per Carton | 8' Lengths Carton Weight | Inside/Outside Corners Pcs Per Carton | Carton Weight |
|-----------------|-----------------|---------------------------|--------------------------|--------------------------|---------------------------------------|---------------|
| Cary 3"         | 3/8"            | 8                         | 64 lf                    | 33 lbs                   | 10                                    | 5 lbs         |
| Cary 4 1/4"     | 3/8"            | 8                         | 64 lf                    | 51 lbs                   | 10                                    | 9 lbs         |
| Ashburn 4"      | 5/16"           | 4                         | 32 lf                    | 42 lbs                   | 10                                    | 9 lbs         |
| Ashburn 4 1/2"  | 5/16"           | 4                         | 32 lf                    | 53 lbs                   | 10                                    | 14 lbs        |
| Franklin 4"     | 1/4"            | 8                         | 64 lf                    | 57 lbs                   | 10                                    | 9 lbs         |
| Franklin 4 1/4" | 1/4"            | 8                         | 64 lf                    | 61 lbs                   | 10                                    | 10 lbs        |
| *Chair Rail 4"  | 1/4"            | 5                         | 60 lf                    | 46 lbs                   | n/a                                   | n/a           |
| Yonkers 6"      | 3/16"           | 4                         | 32 lf                    | 43 lbs                   | 10                                    | 18 lbs        |
| Dearborn 4"     | 1/4"            | 8                         | 64 lf                    | 57 lbs                   | 10                                    | 9 lbs         |
| Dearborn 4"     | 3/8"            | 8                         | 64 lf                    | 59 lbs                   | 10                                    | 9 lbs         |
| Dearborn 4 1/4" | 1/4"            | 8                         | 64 lf                    | 63 lbs                   | 10                                    | 10 lbs        |
| Dearborn 4 1/4" | 3/8"            | 8                         | 64 lf                    | 67 lbs                   | 10                                    | 10 lbs        |
| Dearborn 6"     | 1/4"            | 4                         | 32 lf                    | 54 lbs                   | 10                                    | 24 lbs        |
| Evanston 3"     | 5/16"           | 8                         | 64 lf                    | 52 lbs                   | 10                                    | 9 lbs         |
| Slidell 4 1/4"  | 3/8"            | 8                         | 64 lf                    | 53 lbs                   | 10                                    | 9 lbs         |
| Clayton 3 1/4"  | 3/8"            | 8                         | 64 lf                    | 57 lbs                   | 10                                    | 9 lbs         |
| Preserve 4"     | 5/16"           | 8                         | 64 lf                    | 77 lbs                   | 10                                    | 14 lbs        |
| Preserve 4 1/2" | 5/16"           | 4                         | 32 lf                    | 40 lbs                   | 10                                    | 16 lbs        |
| Decatur 4 1/4"  | 3/8"            | 8                         | 64 lf                    | 53 lbs                   | 10                                    | 9 lbs         |
| *Qtr Round 1/2" | 1/2"            | 20                        | 240 lf                   | 35 lbs                   | n/a                                   | n/a           |
| Alpine 5 1/4"   | 3/8"            | 4                         | 32 lf                    | 52 lbs                   | 10                                    | 21 lbs        |
| Richmond 4"     | 1/4"            | 8                         | 64 lf                    | 57 lbs                   | 10                                    | 9 lbs         |
| Richmond 4"     | 3/8"            | 8                         | 64 lf                    | 59 lbs                   | 10                                    | 10 lbs        |
| Richmond 4 1/4" | 1/4"            | 8                         | 64 lf                    | 61 lbs                   | 10                                    | 10 lbs        |
| Richmond 4 1/4" | 3/8"            | 8                         | 64 lf                    | 59 lbs                   | 10                                    | 10 lbs        |
| York 4"         | 5/16"           | 4                         | 32 lf                    | 40 lbs                   | 10                                    | 16 lbs        |
| York 4 1/2"     | 5/16"           | 4                         | 32 lf                    | 40 lbs                   | 10                                    | 11 lbs        |
| York 6"         | 5/16"           | 4                         | 32 lf                    | 54 lbs                   | 10                                    | 24 lbs        |

\* Indicates Ships in 12' Lengths